

MALLI	Kuivauslämpö + 70C Esim. liete 70% -> 15%		Kuivauslämpö + 70C Esim. hake 50% -> 15%		Kuivauslämpö + 90C Viljat 20% -> 15%		Tehontarve kWe	Max. pituus, m	Kuivurin leveys, m	Kokonais- leveys, m	Max. korkeus, m
	Teho kg/h	Tehontarve, kWth	Teho kg/h	Tehontarve, kWth	Teho kg/h	Tehontarve, kWth					
CD3100	190	140	300	140	2860	180	14	10,00	2,00	5,10	4,00
CD5700	350	250	550	250	4940	340	19	12,50	2,60	5,70	4,00
CD7900	510	370	810	370	6370	500	26	15,00	2,60	5,70	4,00
CD10600	670	480	1060	480	9240	650	35	17,50	2,60	5,70	4,00
CD16000	1080	770	1700	770	13340	1050	52	21,00	3,20	7,00	4,80
CD19400	1250	890	1960	890	16930	1210	57	23,50	3,20	7,00	4,80
CD25600	1680	1200	2650	1200	22300	1630	82	28,50	3,20	6,50	4,80
CD38000	2450	1750	3850	1750	33060	2380	133	39,50	3,20	7,00	5,40
CD60400	3910	2780	6140	2780	52540	3790	244	50,60	3,20	7,50	6,30